

Access Pipe - Oblong Door CIS42



Features and Benefits

- Excellent acoustic properties
- Fully recyclable
- High durability and abrasion resistance
- Optimum corrosion protection
- Sturdy and dimensionally stable
- Rapid and simple assembly

Material Specifications

Description	Materials
Pipe & Door	Grey Cast Iron with lamellar graphite
Coating	Cross-linked red-brown colour resin epoxy coating (40 µm)
Gasket	EPDM
Bolt & Nut	Steel BZP

Product Codes and Dimensions

STOCK NO.	Nominal Diameter (mm)	L(mm)	H(mm)	A(mm)	F(mm)	G (mm)	D (mm)	Weight (KG)
52146	100	340	83	200	230	160	100	7.30
52147 *	125	370	101	225	255	190	125	10.00
52148	150	395	112	250	280	215	150	12.75
52149	200	465	137	300	330	265	200	25.20
52231 *	250	570	170	350	426	330	259	36.00
52232 *	300	640	195	400	476	380	309	51.00

* Special Order / Project Items

Technical Data

- Reaction to fire according to EN 13501: A2. (Non combustible)
- Chemical resistance to wide range: pH2 to pH12
- Tensile strength: ≥ 150 MPa
- Compression strength: ≥ 450 MPa
- Shear strength: ≥ 165 MPa
- Density: approx. 7.2 kg/dm³ (71.5 kN/m³)
- Acoustic rated according to EN 14366:2005
- Low thermal expansion (0.0105 mm/mK)

Applicable Standards

- Pipe and Fittings Standard: EN 877
- Design Standard: DIN 19522
- Quality standard: RAL-GZ 698

