

BLACK PROTECTION BOARD



Product Code	Pricing Unit	Colour	Dimensions	Thickness	Pack Quantity	Pallet Quantity
PBB02	Each	Black	2m x 1m	2mm	25	500
PBB12	Each	Black	2.4m x 1.2m	2mm	25	500
PBB13	Each	Black	2.4m x 1.2m	3mm	20	350
PBB14	Each	Black	2.4m x 1.2m	4mm	10	270
PBB00	Each	Black	1.2m x 1m	2mm	25	500

Product Description:

Proguard Protection Board is manufactured from strong corrugated polypropylene to provide long lasting protection for windows, doors, stairs, walls and floors. Lightweight and extremely strong, the plastic sheets are tear-, puncture- and impact-resistant. They can be cut, curved and creased to fit any surface offering complete surface protection for a variety of applications during refurbishment, building and construction projects.

Proguard Protection Board is similar to twinwall plastic sheeting and correx board, and is ideal for the same uses – i.e. protection for floors and other surfaces.

Benefits:

- Provides efficient protection from knocks, scratches and spills.
- Lightweight and flexible.
- Quick and easy to cut, crease and curved.
- Durable and reusable.
- 100% waterproof.
- Personalised logo and branding printing available.
- Proguard Protection Board is available in translucent, black, flame retardant and a variety of sizes and formats.
- LPS1207 accredited option available.
- Resistant to chemicals.
- 100% Recyclable.

Limitations:

- Non-fire retardant. Use our Flame retardant Proguard Protection Board when this is a requirement.
- Product may become slippery when wet. Mop up any spills immediately or replace where necessary.
- Not suitable for protection against heavy traffic ie. Scissor-lifts. We recommend our Proguard Bufferboard for this application.

Application:

Ensure surfaces onto which Proguard Protection Board is to be laid are free from loose rubble. Beginning from the corner of the room lay the sheets side by side using Proguard Cloth Tape when joining the boards. Use Proguard Low Tack PVC tape when adhering to sensitive surfaces such as marble and glass. To ensure a completely residue-free removal we recommend using Proguard Ultra Low Tack tape.

Performance Data:

Density	2mm (250gsm), 3mm (350gsm), 4mm (600gsm)
Rib Distance	3.2 – 3.5mm
Basic Component	Copolymer polypropylene (C3H6)n(C2H4)m