

Downpipe Bracket

CIS76



Features and Benefits

- Excellent acoustic properties
- Fully recyclable
- High durability and abrasion resistance
- Optimum corrosion protection
- Sturdy and dimensionally stable
- For use with the bearing ring for vertical stack high load applications

Material Specifications

Description	Materials
Core	Grey Cast Iron with lamellar graphite
Coating	Cross-linked red-brown colour resin epoxy coating (40 µm)

Product Codes and Dimensions

STOCK NO.	Nominal Dimension (mm)	L (mm)	D (mm)	Weight (mm)
52201	50	200	87	1.30
52202	70	200	106	1.80
52203	100	200	145	2.70
52204 *	125	200	170	3.00
52205	150	200	195	4.00
52206	200	200	245	5.90
52208 *	250	300	340	18.70

* Special Order / Project Items

Technical Data

- Reaction to fire according to EN 13501: A1. (Non combustible)
- Chemical resistance to wide range: pH2 to pH12
- Tensile strength: ≥ 150 MPa
- Compression strength: ≥ 450 MPa
- Shear strength: ≥ 165 MPa
- Density: approx. 7.2 kg/dm³ (71.5 kN/m³)
- Acoustic rated according to EN 14366:2005
- Low thermal expansion (0.0105 mm/mK)

Applicable Standards

- Pipe and Fittings Standard: EN 877
- Design Standard: DIN 19522
- Quality standard: RAL-GZ 698

