

Copper Press F x F 90° Bend (M-Profile) MCP 10



Features & Benefits

- Durable and secure leak proof joint
- Braze free, permanent joint - no hot works required
- Huge time and resource savings
- 25 Year warranty
- Blue plastic film which will fall off when crimped for easy identification of pressed joint
- 2 point press
- Dust Covers

Material Specifications

NO	Description	Materials
1	Body	Cu-DHP (CW024A)
2	Crimp indicator film	PVC, Blue
3	O-Ring	EPDM
4	Dust Cap	PE

Product Codes and Dimensions

STOCK NO.	D1	D2	D3	D4	A1	L1
27810	15	15.6	18	23	19	47
27811	22	22.8	25	31.3	20	60
27812	28	28.8	31	37.4	22	73
27813	35	35.7	38.3	44.7	25	84
27814	42	42.8	45.3	53.5	29	99
27815	54	54.8	57.3	65.3	34	126
27816	67	69.1	71.7	82.6	48	163
27817	76	78.6	81.1	94.4	49	186
27819	108	110.9	113.8	132.1	65	256

Technical Data

- Working Pressure 16 Bar @ 95°C
- "M" profile press jaws or slings
- Approved tools include Novapress, REMS, Rothenberger and Ridgid

Applicable Standards

- WRAS approved
- For use with type TX copper tubing conformant to EN 1057
- Manufactured to EN1254 standard

