

Stainless Press Fitting Reducer MSP03



Features and Benefits

- Suitable for Potable water, Cooling systems, Industrial applications
- High grade Stainless Steel is extremely durable and corrosion resistant
- Blue plastic film which will fall off when crimped for easy identification of pressed joint
- Dust covers
- 30 Year Warranty

Material Specifications

Description	Materials
Body	316L Stainless Steel
Crimp indicator film	PVC, Blue
O-Ring	EPDM
Dust Cap	PE

Product Codes and Dimensions

STOCK NO.	D (mm)	d (mm)	L (mm)	Z (mm)
29459	22	15	62	42
29460	28	15	63	43
29461	28	22	66	45
29462	35	22	68	47
29463	35	28	76	53
29464	42	22	84	63
29465	42	28	82	59
29466	42	35	80	54
29467	54	28	98	75
29468	54	35	96	70
29469	54	42	102	72
29470	76	54	145	110
29471	89	54	147	112
29472	89	76	161	108
29473	108	54	162	127
29474	108	76	176	123
29475	108	89	203	143

Technical Data

- Operating temperature -20°C ~ +120°C
- 316L Stainless Steel fitting
- EPDM Sealing ring
- "M" Profile Press Jaws or slings
- Approved tools include Novapress, REMS, Rothenberger and Ridgid
- Max Working Pressure
 - 15mm - 28mm : 40 bar
 - 35mm - 54mm : 25 bar
 - 76mm - 108mm : 16 bar

Applicable Standards

- WRAS Approved
- 316L grade stainless steel fitting
- DVGW-W534

