

Single Elbows 68°

CIS18



Features and Benefits

- Excellent acoustic properties
- Fully recyclable
- High durability and abrasion resistance
- Optimum corrosion protection
- Sturdy and dimensionally stable
- Rapid and simple assembly

Material Specifications

Description	Materials
Core	Grey Cast Iron with lamellar graphite
Coating	Cross-linked red-brown colour resin epoxy coating (40 µm)

Product Codes and Dimensions

STOCK NO.	Nominal Diameter (mm)	X (mm)	Weight (Kg)
52065	50	65	0.70
52066	70	75	1.10
52067	100	90	1.90
52068 *	125	105	2.90
52069	150	120	4.10
52070	200	145	7.70

* Special Order / Project Items

Technical Data

- Reaction to fire according to EN 13501: A1. (Non combustible)
- Chemical resistance to wide range: pH2 to pH12
- Tensile strength: ≥ 150 MPa
- Compression strength: ≥ 450 MPa
- Shear strength: ≥ 165 MPa
- Density: approx. 7.2 kg/dm³ (71.5 kN/m³)
- Acoustic rated according to EN 14366:2005
- Low thermal expansion (0.0105 mm/mK)

Applicable Standards

- Pipe and Fittings Standard: EN 877
- Design Standard: DIN 19522
- Quality standard: RAL-GZ 698

