# **Eres** heating expansion vessels

#### Introduction

Eres expansion vessels are manufactured to meet the requirements of PED 97/23/EC Directive, and BS EN 13831:2007 'Closed expansion vessels with built in diaphragm for installation in water'.

## Design

The vessels are fabricated by welding the various sections together which results in a very reliable structure suitable for internal pressures up to 6 bar.

Epoxy coated and available in red.

Non-replaceable diaphragm held securely in place by a flange.

The 35 to 300 litre vessels have a top water connection and the 500 to 1000 litre vessels have a bottom connection.

Suitable for temperatures up to 100°C, resistant to ethylene or propylene glycol mixtures and has low gas permeability.

In the event that the diaphragm within the expansion vessel could be subjected to continuos temperatures above 100°C, the vessel must be protected by an additional vessel (VDI 6002 directive).

### **Technical Data**

Max. working pressure:

5 to 25 litres 5 bar
35 to 50 litres 4 bar
80 to 1000 litres 6 bar


Operating temperature range: -10 to 100°C

Factory air pre-charge pressure: 1.5 bar


#### Materials

Shell: carbon steel
Connections: carbon steel
Diaphragm elastomer: synthetic
Coating: epoxy powder

## Dimensions



Prod Code	Capacity	ØD	Н	С
ER-08LTVESS	8 litres	200	335	G¾B
ER-12LTVESS	12	270	320	G¾B
ER-18LTVESS	18	270	415	G¾B
ER-24LTVESS	24	320	440	G¾B



Prod Code	Capacity	ØD	Н	С
ER-35LTVESS	35 litres	360	475	G¾B
ER-50LTVESS	50	360	600	G¾B
ER-80LTVESS	80	485	570	G1B
ER-100LTVESS	100	485	650	G1B
ER-140LTVESS	140	485	935	G1B
ER-200LTVESS	200	600	860	G1B
ER-300LTVESS	300	600	1,245	G1B
ER-500LTVESS	500	750	1,445	G1B
ER-1000LTVESS	1000	750	2,555	G1B

Altecnic Ltd Mustang Drive, Stafford, Staffordshire ST16 1GW T: +44 (0)1785 218200 E: sales@altecnic.co.uk Registered in England No: 2095101

altecnic.co.uk

E & O.E

© Altecnic Limited. 2021 ALTECNIC™

